

- Type: Permanent, round, coloured pencils
- Lead: permanent, creamy lead, 3.8 diameter, maximum covering power, high pigment concentration for intense, bright colours
- Light resistance complies with the highest international standards for light resistance in coloured pencils: ASTM D6901

• Pencil: round, 8 ply, matt casing matches the colour of the lead, colour number and name indicated. The pencils wood casings are made of environmentally friendly California cedar.



| LUMINANCE 6901 | ILEUG<br>(EY 8:<br>755 |  | ~~           |
|----------------|------------------------|--|--------------|
|                | MINANCE 6901           |  | MINANCE 6901 |
|                | ľΩΊ                    | The second secon | In           |
|                |                        | The second name and district to the second name and address of |              |



This standard specification establishes quality requirements for composition, performance, and labeling of artists' colored pencils. This specification also covers vehicles and additives. With LFI being the highest & LFII being the second highest.

| Colour Number | Colour              | Lightfastness |
|---------------|---------------------|---------------|
| 001           | White               | LFI           |
| 009           | Black               | LFI           |
| 030           | Orange              | LFI           |
| 061           | Permanent Red       | LFI           |
| 159           | Prussian Blue       | LFI           |
| 162           | Phthalocyanine Blue | LFI           |
| 220           | Grass Green         | LFI           |
| 240           | Lemon Yellow        | LFI           |
| 470           | Spring Green        | LFI           |
| 571           | Anthraquinoid       | LFI           |
| 585           | Perylene Brown      | LFII          |
| 661           | Light Blue Cobalt   | LFI           |